

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (Original) A piezoelectric pump drive circuit comprising:
a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;
a voltage-boosting means for converting a low-voltage power supply to a high voltage; and
an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;
wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier.

2. (Original) A piezoelectric pump drive circuit comprising:
a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;
a voltage-boosting means for converting a low-voltage power supply to a high voltage;
an amplification means driven by high voltage generated by said voltage-boosting means for

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave; and
control means for implementing variable frequency control over three or more different frequencies at the time of activation of said sine wave oscillation means.

3. (Currently Amended) A piezoelectric pump drive circuit comprising:
a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;
a voltage-boosting means for converting a low-voltage power supply to a high voltage;
an amplification means composed of a D-class amplifier driven by high voltage generated by said voltage-boosting means for subjecting a ~~for amplifying the~~ signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification, and a low-pass filter for demodulating the output signal of said D-class amplifier; said amplification means being driven at high voltage generated by said voltage-boosting means and amplifying the signal supplied as output from said sine wave oscillation means for driving said piezoelectric element ~~and for driving said piezoelectric element by a high-voltage sine wave; and~~
a control means for implementing variable frequency control over three or more different frequencies ~~of the frequency~~ at the time of activation of said sine wave oscillation means;
~~wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low pass filter for demodulating the output signal of said D-class amplifier.~~

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

4. (Currently Amended) A piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means composed of a D-class amplifier driven by high voltage generated by said voltage-boosting means for subjecting a ~~for amplifying the~~ signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification , and low-pass filter for demodulating the output signal of said D-class amplifier; said amplification means being driven at high voltage generated by said voltage-boosting means and amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

a temperature sensing means for sensing temperature; and

a control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means.

5. (Original) A piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

a temperature sensing means for sensing temperature; and

a control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier.

6. (Original) A piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

a first control means for implementing variable frequency control at the time of activation of said sine wave oscillation means;

a temperature sensing means for sensing temperature; and

a second control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means.

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

7. (Original) A piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

a first control means for implementing variable frequency control at the time of activation of said sine wave oscillation means;

a temperature sensing means for sensing temperature; and

a second control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier.

8. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage; and

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier;

a heat sink that contacts a heat-generating body;

a radiator for radiating heat to the outside;

coolant circulation passages connected such that coolant circulates between said heat sink and said radiator; and

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating coolant in said coolant circulation passages.

9. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave; and

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

control means for implementing variable frequency control over three or more different frequencies at the time of activation of said sine wave oscillation means;

a heat sink that contacts a heat-generating body;

a radiator for radiating heat to the outside;

coolant circulation passages connected such that coolant circulates between said heat sink and said radiator;

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating coolant in said coolant circulation passages.

10. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave; and

a control means for implementing variable frequency control at the time of activation of said sine wave oscillation means;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

filter for demodulating the output signal of said D-class amplifier;
a heat sink that contacts a heat-generating body;
a radiator for radiating heat to the outside;
coolant circulation passages connected such that coolant circulates between said heat sink and
said radiator; and
a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating
coolant in said coolant circulation passages.

11. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:
a sine wave oscillation means for generating a sine wave signal of the frequency that drives a
piezoelectric element of a piezoelectric pump;
a voltage-boosting means for converting a low-voltage power supply to a high voltage;
an amplification means driven by high voltage generated by said voltage-boosting means for
amplifying the signal supplied as output from said sine wave oscillation means and for driving
said piezoelectric element by a high-voltage sine wave;
a temperature sensing means for sensing temperature; and
a control means for adjusting the signal amplitude of said sine wave oscillation means in
accordance with the sensed temperature of said temperature sensing means;
a heat sink that contacts a heat-generating body;
a radiator for radiating heat to the outside;
coolant circulation passages connected such that coolant circulates between said heat sink and

PRELIMINARY AMENDMENT
New U.S. National Stage Entry of PCT/JP2005/001389

said radiator; and

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating coolant in said coolant circulation passages.

12. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

a temperature sensing means for sensing temperature; and

a control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier;

a heat sink that contacts a heat-generating body;

a radiator for radiating heat to the outside;

coolant circulation passages connected such that coolant circulates between said heat sink and

PRELIMINARY AMENDMENT
New U.S. National Stage Entry of PCT/JP2005/001389

said radiator; and

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating coolant in said coolant circulation passages.

13. (Original) A cooling system comprising:
- a piezoelectric pump drive circuit comprising:
 - a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;
 - a voltage-boosting means for converting a low-voltage power supply to a high voltage;
 - an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;
 - a first control means for implementing variable frequency control at the time of activation of said sine wave oscillation means;
 - a temperature sensing means for sensing temperature; and
 - a second control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means;
 - a heat sink that contacts a heat-generating body;
 - a radiator for radiating heat to the outside;
 - coolant circulation passages connected such that coolant circulates between said heat sink and said radiator; and

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating coolant in said coolant circulation passages.

14. (Original) A cooling system comprising:

a piezoelectric pump drive circuit comprising:

a sine wave oscillation means for generating a sine wave signal of the frequency that drives a piezoelectric element of a piezoelectric pump;

a voltage-boosting means for converting a low-voltage power supply to a high voltage;

an amplification means driven by high voltage generated by said voltage-boosting means for amplifying the signal supplied as output from said sine wave oscillation means and for driving said piezoelectric element by a high-voltage sine wave;

a first control means for implementing variable frequency control at the time of activation of said sine wave oscillation means;

a temperature sensing means for sensing temperature; and

a second control means for adjusting the signal amplitude of said sine wave oscillation means in accordance with the sensed temperature of said temperature sensing means;

wherein said amplification means is composed of: a D-class amplifier driven by a high voltage generated by said voltage-boosting means for subjecting the signal supplied as output from said sine wave oscillation means to pulse-width modulation to realize amplification; and a low-pass filter for demodulating the output signal of said D-class amplifier;

a heat sink that contacts a heat-generating body;

a radiator for radiating heat to the outside;

PRELIMINARY AMENDMENT

New U.S. National Stage Entry of PCT/JP2005/001389

coolant circulation passages connected such that coolant circulates between said heat sink and

said radiator; and

a piezoelectric pump that is driven by said piezoelectric pump drive circuit for circulating

coolant in said coolant circulation passages.